

Glo-Ray® Designer **Portable Heated Shelves**

Models: GR2S-24, -30, -36, -42, -48, -54, -60, -66, -72

Hatco Glo-Ray® Designer Portable Heated Shelves use a blanket heating element to extend the holding time of food while keeping it at optimum serving temperatures. Perfect for when a heated workspace is needed, or for extra base heat in a pass-through or buffet area. The modern design is perfect for front-of-the-house use. Seven Designer powdercoated colors blend these units into any décor while providing a durable, easy-to-clean surface.

Standard features

- Thermostatically-controlled hardcoated heated base has a temperature range of 80° to 200°F (27°-93°C)
- Heated surface widths from 23.75" to 71.75" (603-1822 mm)
- Overall widths of 30,25" to 78,25" (768-1988 mm)
- Rounded edges and hardcoated aluminum surface offer a modern style for front-of-the-house applications
- Unit comes standard with black inset panels
- Features a 6' (1829 mm) cord and plug set which allows heat to be placed where it is needed the most
- 4" (102 mm) legs standard on GR2S-30 and wider models

Project _	
Item #	
Quantity	





Options (available at time of purchase only)

Designer Color base (top surface not painted) - Clear Anodized Aluminum Standard - Non-standard colors are non-returnable -☐ Warm Red ☐ White Granite □Black ☐ Grav Granite

☐ Hunter Green □ Navy Blue ☐ Antique Copper

Designer Color Inset Panel - Black Standard - Non-standard colors are nonreturnable •

□ Warm Red ☐ Gray Granite ☐ White Granite ☐ Navy Blue ☐ Hunter Green ☐ Antique Copper

Designer Corner Caps

Non-standard colors are non-returnable – Black Standard

☐ Dark Gray

Accessories

 \Box 4" (102 mm) adjustable Legs for GR2S-24 (standard on GR2S-30 and larger)

Trivets - Stainless Steel

☐ Half-size 10.2"W x 7.6"D x" (259 x 194 mm)

☐ Full-size 10.125"W x 18"D x (257 x 457 mm)

Stainless Steel Food Holding Pans

☐ Third-size 12.75"W x 6.9" D x 2.5"H (324 x 175 x 64 mm) ☐ Half-size 12.75"W x 10.4"D x 2.5"H (324 x 264 x 64 mm) □ Full-size 12.75"W x 20.75"D x 2.5"H (324 x 527 x 64 mm) □ Full-size 12.75"W x 20.75"D x 4"H (324 x 527 x 102 mm)





IFS anti-microbial coatings use naturally-occurring, environmentally sustainable, silver ions to help inhibit the growth of microbes on the powder coated surface. See www.hatcocorp.com/antimicrobial-paint for more information.



For operation, location and safety information, please refer to the Installation and Operating Manual.












Glo-Ray® Designer Portable Heated Shelves

Models: GR2S-24, -30, -36, -42, -48, -54, -60, -66, -72



SPECIFICATIONS Glo-Ray® Designer Portable Heated Shelves

The shaded areas contain electrical information for International models

	Decigner i di table l'icatea cheives								
	Dimensions	Heated Base	Maximum Full-size Pan Capacity						
	WxDxH	Surface	12.75"W x 20.75"D				Plug	Approx.	
Model [®]	(height includes legs)	WxD	(324 x 527 mm)	Volts	Watts	Amps	Configuration	Ship Weight	
GR2S-24	30.25" x 27" x 4" (768 x 686 x 102 mm) on 1" (25 mm) legs	23.75" x 21.75" (603 x 552 mm)	1 full-size pan	100	350	3.5	NEMA 5-15P	37 lbs. (17 kg.)	
				120	350	2.9	NEMA 5-15P		
				220	350	1.6	CEE 7/7 Schuko		
				240		1.5	BS-1363		
GR2S-30*	36.25" x 27" x 7" (921 x 686 x 178 mm) on 4" (102 mm) legs	29.75" x 21.75" (756 x 552 mm)	2 full-size pans	100	450	4.5	NEMA 5-15P	40 lbs. (18 kg.)	
				120	450	3.8	NEMA 5-15P		
				220	450	2.0	CEE 7/7 Schuko		
				240		1.9	BS-1363		
GR2S-36*	42.25" x 27" x 7" (1073 x 686 x 178 mm) on 4" (102 mm) legs	35.75" x 21.75" (908 x 552 mm)	2 full-size pans	100	550	5.5	NEMA 5-15P	45 lbs. (20 kg.)	
				120	550	4.6	NEMA 5-15P		
				220	550	2.5	CEE 7/7 Schuko		
				240		2.3	BS-1363		
GR2S-42*	48.25" x 27" x 7" (1226 x 686 x 178 mm) on 4" (102 mm) legs	41.75" x 21.75" (1060 x 552 mm)	3 full-size pans	100	600	6.0	NEMA 5-15P	51 lbs. (23 kg.)	
				120	600	5.0	NEMA 5-15P		
				220	600	2.7	CEE 7/7 Schuko		
				240		2.5	BS-1363		
GR2S-48*	54.25" x 27" x 7" (1378 x 686 x 178 mm) on 4" (102 mm) legs	47.75" x 21.75" (1213 x 552 mm)	3 full-size pans	120	700	5.8	NEMA 5-15P	56 lbs. (26 kg.)	
				220	700	3.2	CEE 7/7 Schuko		
				240		2.9	BS-1363		
GR2S-54*	60.25" x 27" x 7" (1530 x 686 x 178 mm) on 4" (102 mm) legs	53.75" x 21.75" (1365 x 552 mm)	4 full-size pans	120	800	6.7	NEMA 5-15P	61 lbs. (28 kg.)	
				220	800	3.6	CEE 7/7 Schuko		
				240		3.3	BS-1363		
GR2S-60*	66.25" x 27" x 7" (1683 x 686 x 178 mm) on 4" (102 mm) legs	59.75" x 21.75" (1518 x 552 mm)	4 full-size pans	120	900	7.5	NEMA 5-15P	70 lbs. (32 kg.)	
				220	900	4.1	CEE 7/7 Schuko		
				240		3.8	BS-1363		
GR2S-66*	72.25" x 27" x 7" (1835 x 686 x 178 mm) on 4" (102 mm) legs	65.75" x 21.75" (1670 x 552 mm)	5 full-size pans	120	1000	8.3	NEMA 5-15P	75 lbs. (34 kg.)	
				220	1000	4.5	CEE 7/7 Schuko		
				240		4.2	BS-1363		
	78.25" x 27" x 7"			120	1100	9.2	NEMA 5-15P	82 lbs.	
GR2S-72*	(1988 x 686 x 178 mm) on 4" (102 mm) legs	71.75" x 21.75" (1822 x 552 mm)	5 full-size pans	220	1100	5.0	CEE 7/7 Schuko	(38 kg.)	
				240		4.6	BS-1363		

[®] When no color is specified, color inset panels and corner caps will be Black.

CORD LOCATION

Center on bottom on control panel.

PRODUCT SPECS Glo-Ray® Designer Portable Heated Shelves

The infrared Designer Portable Heated Shelf shall be a Glo-Ray® Model ... as manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The warmer shall be rated at ... watts, ... volts, and be ... inches (millimeters) in overall width. It shall consist of a thermostatically-controlled heated base, Black Designer Color inset panels, Black Corner Caps and a cord with plug attached.

PLUG CONFIGURATIONS



Options shall include: Designer Color Inset Panels, Designer Color Base and Gray Corner Caps. Accessories shall include 4" (102 mm) adjustable legs, stainless steel food pans, and stainless steel trivets.

Warranty consists of 24/7 parts and service assistance (U.S. and Canada only).

HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. | (414) 671-6350



www.hatcocorp.com | support@hatcocorp.com | Find a Hatco Rep | Image Library | Document Library | Patents | Chat

[◆] NSF requires units over 36" (914 mm) in width or weighing more than 80 lbs. (36 kg) be either sealed to or raised on the installation surface with 4" (102 mm) legs included.