


# Toast-Qwik® Electric **Conveyor Toasters**


Models: TQ3-20, -20H

Hatco's next generation of Toast-Qwik® Conveyor Toasters have been designed to provide a great look, and increased production capabilities. They continue to provide the best reliability, flexibility and value of any convevor toaster available!

### **Standard features**

- Patented ColorGuard Sensing System continually monitors chamber temperature and adjusts the chamber to ensure consistent toast results - even in your busiest periods
- Power Save mode activates manually by pressing the Power Save Button above the leaf symbol, which reduces power by 50%
- Features an Air Intake Filter Screen which is removable for easy cleaning
- Crumb tray is removable
- 2" (51 mm) high opening for standard TQ3-20 unit
- 3" (76 mm) high for TQ3-20H unit, which is better for use with thicker breads and rolls
- DC stepper motor provides wide range of linear and precise speed control
- TQ3-20 and TQ3-20H models produce between 600-700 slices of toast per hour
- Double-sided or single-sided toasting at the touch of a button







**Options** (available at time of purchase *only*)

Designer Colors

Non-standard colors are non-returnable – Designer Black standard ☐ Warm Red ☐ Stainless Steel

- ☐ Stainless Steel toast tray insert
- □ Extended feed ramp in lieu of existing ramp adds 3" (76 mm)
- □XL extended feed ramp in lieu of existing ramp adds 9" (229 mm)

IFS anti-microbial coatings use naturally-occurring, environmentally sustainable, silver ions to help inhibit the growth of microbes on the powder coated surface. See www.hatcocorp.com/antimicrobial-paint for more information.



For operation, location and safety information, please refer to the Installation and Operating Manual.













## Toast-Qwik® Electric Conveyor Toasters

Models: TQ3-20,-20H

### TQ3-20, -20H





#### **SPECIFICATIONS** Toast-Qwik® Conveyor Toasters

The shaded areas contain electrical

Toast-Qwik Conveyor Toasters							information for International models	
Model	Opening Dimensions (W x H)	Dimensions (W x D x H)	Volts Single Phase	Hertz	Watts	Amps	Plug	Approx. Ship Weight
TQ3-20	10.37" x 2" (263 x 51 mm)	14.70" x 20.67" x 17.14" (373 x 525 x 435 mm)	200	50/60	2284	11.4	No Plug	54 lbs. (25 kg)
			220	60	2260	10.3	BS 1363	
			208	50/60	2470	11.9	NEMA 6-15P	
			240			10.3		
			220-230 (CE)	50/60	2260-2470	10.3-10.7	Schuko, CCC or No Plug	
			230-240 (CE)		2268-2470	9.9-10.3	Schuko, BS-1363 or AS 3112	
TQ3-20H	10.37" x 3" (263 x 76 mm)	14.70" x 20.67" x 17.14" (373 x 525 x 435 mm)	200	50/60	2472	12.1	No Plug	54 lbs. (25 kg)
			220	60	2397	10.9	BS 1363	
			208	50/60	2620	12.6	NEMA 6-20P	
			220	60	2397	11.9		
			240	50/60	2620	10.9	NEMA 6-15P	
			220-230 (CE)	50/60	2397-2620	10.9-11.4	Schuko, CCC or No Plug	
			230-240 (CE)	50/60	2406-2620	10.5-10.9	Schuko, BS-1363, No Plug or AS 3112	

#### **CORD LOCATION**

Lower right corner on back of unit.

#### **PLUG CONFIGURATIONS**

**NEMA 6-15P** 

**NEMA 6-20P** 

CEE 7/7 Schuko

CCC

BS-1363

AS 3112













#### **PRODUCT SPECS**

#### Toast-Quik® Electric Conveyor Toasters

The electric Toast-Qwik® Conveyor Toaster with patented ColorGuard Sensing System shall be a Hatco model ... as manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The toaster shall have the capacity to toast up to ... pieces per hour and it shall be rated at ... kW, ... volts, single phase. The toaster shall be of powdercoated steel

design and shall include double- or single-sided toasting capabilities, manual power save mode, a removable/cleanable air intake filter screen, and variable speed control. The toaster will have metal sheathed heating elements and factory attached UL listed

Warranty consists of 24/7 parts and service assistance (US and Canada only).

HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. | (414) 671-6350

www.hatcocorp.com support@hatcocorp.com Find a Hatco Rep Image Library Document Library Patents Chat