

MAX WATT

INFRARED STRIP HEATERS


GRAML-48 with
Remote Control Enclosure



MAXIMIZE YOUR HOLDING PERFORMANCE WITH 25% MORE POWER BEHIND YOU

The Hatco Max Watt® Infrared Strip Heaters safely hold the temperature of your product without drying out or further cooking food. The end result is hot, fresh food that's ready-to-serve. The continuous aluminum housing and heavy-duty mountings ensure the durability and quality of Hatco products.

- Features 25% greater wattage output than Glo-Ray high watt by comparison with single units varying in watts from 450 to 4150 watts; and units with lights varying from 570 to 4870 watts
- Sturdy extruded aluminum housings that do not sag from 18" to 72" (457 to 1829 mm) in 6" (152 mm) increments and 84" to 144" (2134 to 3658 mm) in 12" (305 mm) increments
- Heavy-duty insulation minimizes heat loss
- Shatter-resistant incandescent lights (standard) enhance product display while safeguarding food products from bulb breakage. An optional halogen bulb may be used in lieu of incandescents
- Available in seven *Designer Colors* and five *Gloss Finishes*



MAXWELL WATT
HATCO'S SECRET AGENT IN FOODWARMING



GRAML-54D

DESIGNER COLORS

Warm Red

Gray Granite

Navy Blue

Black

White Granite

Hunter Green

Antique Copper

GLOSS FINISHES

Radiant Red

Glossy Gray

Bold Black

Gleaming Gold

Brilliant Blue




DUAL MODELS AVAILABLE. FOR MORE INFORMATION, SEE GRAM-D SPEC SHEET



GLO-RAY[®] MAX WATT INFRARED FOODWARMERS

Models GRAM-18, -24, -30, -36, -42, -48, -54, -60, -66, -72, -84, -96, -108, -120, -132, -144
GRAML-18, -24, -30, -36, -42, -48, -54, -60, -66, -72, -84, -96, -108, -120, -132, -144



SPECIFICATION*

Aluminum Max Watt		Aluminum Max Watt with Lights			
Model	Watt	Model	Watt	Width	Shipping Weight
GRAM-18	450	GRAML-18	570	18" (457 mm)	6 lbs (3 kg)/ 9 lbs (4 kg)
GRAM-24	650	GRAML-24	770	24" (610 mm)	7 lbs (3 kg)/10 lbs (5 kg)
GRAM-30	825	GRAML-30	945	30" (762 mm)	8 lbs (4 kg)/11 lbs (5 kg)
GRAM-36	1000	GRAML-36	1180	36" (914 mm)	9 lbs (4 kg)/13 lbs (6 kg)
GRAM-42	1175	GRAML-42	1355	42" (1067 mm)	10 lbs (5 kg)/15 lbs (7 kg)
GRAM-48	1300	GRAML-48	1540	48" (1219 mm)	11 lbs (5 kg)/17 lbs (8 kg)
GRAM-54	1500	GRAML-54	1740	54" (1372 mm)	13 lbs (6 kg)/19 lbs (9 kg)
GRAM-60	1700	GRAML-60	2000	60" (1524 mm)	14 lbs (6 kg)/21 lbs (10 kg)
GRAM-66	1875	GRAML-66	2175	66" (1676 mm)	16 lbs (7 kg)/22 lbs (10 kg)
GRAM-72	2075	GRAML-72	2435	72" (1829 mm)	17 lbs (8 kg)/24 lbs (11 kg)
GRAM-84	2400	GRAML-84	2820	84" (2134 mm)	19 lbs (9 kg)/ 28 lbs (13 kg)
GRAM-96	2675	GRAML-96	3155	96" (2438 mm)	21 lbs (10 kg)/ 32 lbs (15 kg)
GRAM-108**	3000	GRAML-108**	3540	108" (2743 mm)	23 lbs (10 kg)/36 lbs (16 kg)
GRAM-120**	3400	GRAML-120**	4000	120" (3048 mm)	26 lbs (12 kg)/40 lbs (18 kg)
GRAM-132**	3750	GRAML-132**	4410	132" (3353 mm)	30 lbs (14 kg)/ 44 lbs (20 kg)
GRAM-144**	4150	GRAML-144**	4870	144" (3658 mm)	33 lbs (15 kg)/ 48 lbs (22 kg)

- ✦ Includes either attached control or Remote Control Enclosure with toggle switch(es) and indicator light(s).
- ✧ Add 2-8 lbs. (1-3 kg) depending on RMB.
- ▲ Models require tandem (end-to-end) elements, see tandem option for additional charges.
- 120 volt models available with RMB only.
- ! 120/208 and 120/240 volt models available with RMB only.
- * 120 volt models not available.

DIMENSIONS

GRAM: 18" to 144"W x 6"D x 2 1/2"H (457-3658 x 152 x 64 mm).
GRAML: 18" to 144"W x 9"D x 2 1/2"H (457-3658 x 229 x 64 mm).
For special widths, consult factory.

VOLTAGE

120, 208 and 240 volts, single phase. Models with Lights rated 120, 120/208 or 120/240 volts, single phase.

MOUNTING REQUIREMENTS

Recommended Mounting Height: 14"-18" (356-457 mm)


Adjustable Angle Brackets (Provides 1" - 2" (25-51 mm) clearance above Glo-Ray unit)

MINIMUM SPACING -

GLO-RAY MAX WATT FOODWARMERS MAY NOT BE INSTALLED IN COMBUSTIBLE SURROUNDINGS.

Non-Combustibles: Pass through area: 1" (25 mm) above, 12" (305 mm) to surface below. Corner mount: 3" (76 mm) from non-combustible back wall 12" (305 mm) to surface below. Cord connected: 3" (76 mm) below an overshelf, 12" (305 mm) to surface below. Maximum 10" (254 mm) setback from the front of an overshelf.

PLUG CONFIGURATION



120 volts only - Models 48" (1219 mm) or less with Chain kit only.

OPTIONS (NOT FOR RETROFIT)

- Designer Colors: Warm Red, Black, Gray Granite, White Granite, Navy Blue, Hunter Green, Antique Copper
- Gloss Finishes: Smooth White, Gleaming Gold, Glossy Gray, Bold Black, Radiant Red, Brilliant Blue
- Indicator Light
- Tandem Charge (Max. two elements end-to-end)
- Extended Electrical Leads
- Halogen Bulb in lieu of Standard Display Light
- Remote Control Enclosure with Toggle Switch(s) and Indicator Light(s) (In lieu of attached Control Enclosure)

- Remote Control Enclosure with Toggle Switch, Electronic Infinite Control, Relay, and Indicator Light (In lieu of attached Control Enclosure)
- Non-Adjustable Tubular Stands 12", 14", 16", 18", 20", or 24" (305, 356, 406, 457, 508, or 610 mm) - Available in Designer colors or Gloss finishes
- 6' (1829 mm) Cord and Plug Set (120V only) on models up to 48" (1219 mm) with Standard Chain Mount Kit (Two S Hooks with Two 6" Lengths of Chain)

ACCESSORIES

- Chain and S Hook Suspension

PRODUCT SPECS Infrared Foodwarmer

The Infrared Foodwarmer shall be a Glo-Ray[®], manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The Foodwarmer shall be a Glo-Ray Model ..., rated at ...watts, ...volts, single phase and be ...millimeters in overall width.

The Glo-Ray shall consist of an aluminum housing and include as standard equipment adjustable angle brackets.

The infrared heating element shall be tubular metal sheathed. The foodwarmer shall be factory assembled ready for electrical installation.

Accessories shall include suspension chain and fittings.

HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. • (800) 558-0607 • (414) 671-6350
Fax (800) 543-7521 • Int'l. Fax (414) 671-3976 • www.hatcocorp.com • E-mail: equipsales@hatcocorp.com