



Glo-Ray® Designer Infrared Aluminium Strip Heaters with Lights

Models:

GR2AL -18, -24, -30, -36, -42, -48, -54, -60, -66, -72, -84
GR2AHL-18, -24, -30, -36, -42, -48, -54, -60, -66, -72, -84

Hatco Glo-Ray® Infrared Aluminum *Designer* Strip Heaters with lights safely keep all hot foods at optimum serving temperatures longer. This modern design is ideal for front-of-the-house use. Units are offered in continuous housings up to 84" (2134 mm), are available in *Designer* colors to match most décors.


Standard features

- Pre-focused heat maintains safe serving temperatures longer without continuing to cook the food
- Sturdy continuous aluminum housings eliminate sagging
- Widths from 21.5" to 87.5" (546 X 2223 mm)
- 14" (356 mm) *Designer* non-adjustable Stands Standard
- Available in a variety of models, configurations, colors and accessories to provide unlimited flexibility
- Designer colors and inset panels allow the unit to match surrounding décor
- Black corner caps and inset panels standard
- Standard coated shatter-resistant incandescent or optional halogen lights enhance product displays while safeguarding food from bulb breakage
- Optional sneeze guards
- Remote control installation is required - must chose RMB
- Additional reflector styles and lower wattage elements available, consult factory for more information

Project _____


Item # _____

Quantity _____



GR2AHL-36
Optional Overhead Mounts,
Designer color Inset Panels
(black corner Caps Standard)

GR2AHL-24
with standard *Designer*
non-adjustable Stands, black
Corner Caps and Optional
Sneeze Guards, *Designer*
color Inset Panels



Options (available at time of purchase only)

Housing – 12" (305 mm)

Designer Color – Aluminum finish standard†

- ☐ Warm Red ☐ Black ☐ Gray Granite ☐ White Granite
☐ Navy Blue ☐ Hunter Green ☐ Antique Copper

Inset Panel *Designer* color – Black standard†

- ☐ Warm Red ☐ Black ☐ Gray Granite ☐ White Granite
☐ Navy Blue ☐ Hunter Green ☐ Antique Copper

Corner Caps *Designer* color, Black standard†

- ☐ Black ☐ Dark Gray

☐ No Control (GR2AL only) – requires selection of RMB2-xx control

Remote Box, *Designer* color – Aluminum finish Standard†

- ☐ Warm Red ☐ Black ☐ Gray Granite ☐ White Granite
☐ Navy Blue ☐ Hunter Green ☐ Antique Copper

Sneeze Guards

- ☐ 7.5" (191 mm) – One Side ☐ 7.5" (191 mm) – Two Sides
☐ 14" (356 mm) – One Side ☐ 14" (356 mm) – Two Sides

Designer Non-Adjustable Stands – 14" (356 mm) *Designer* Stand standard

- ☐ 10" (254 mm) ☐ 12" (305 mm) ☐ 16" (406 mm)

Designer Color – Aluminum finish standard†

- ☐ Warm Red ☐ Black ☐ Gray Granite ☐ White Granite
☐ Navy Blue ☐ Hunter Green ☐ Antique Copper

☐ Overhead Mounts 4" (102 mm) in lieu of 14" (356 mm) standard Stands

Designer Color – Aluminum finish standard†

- ☐ Warm Red ☐ Black ☐ Gray Granite ☐ White Granite
☐ Navy Blue ☐ Hunter Green ☐ Antique Copper

☐ No Bulbs

☐ Extra Lamps – Installed (max. two per ft. less one – one per ft. is standard)

Extended Electrical Leads

- ☐ 1'-5' (305-1525 mm) ☐ 6'-10' (1829-3048 mm)
☐ 11'-15' (3352-4572 mm) ☐ 16'-20' (4877-6096 mm)

Accessories

ChefLED bulb 120V

- ☐ 2700K Warm Light ☐ 3000K Warm Light ☐ 4000K Cool Light

†Non-standard color are non-returnable



ANSI/NSF 4



HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A.

(800) 558-0607 | (414) 671-6350 | www.hatcocorp.com | support@hatcocorp.com | intl@hatcocorp.com




Glo-Ray® Infrared Designer Aluminum Strip Heaters with Lights

Models: GR2AL -18, -24, -30, -36, -42, -48, -54, -60, -66, -72, -84

GR2AHL-18, -24, -30, -36, -42, -48, -54, -60, -66, -72, -84

GR2AL and GR2AHL



SPECIFICATIONS

Glo-Ray® Infrared Designer Aluminum Strip Heaters with Lights

Dimensions (without Non-Adjustable Stands)

21.5" - 87.5" W x 11.91" D x 3.5" H (546 - 2223 mm x 303 mm x 89 mm)

Standard Watt				High Watt				Both Models	
Model	Volts single phase	Watt	Amps	Model	Volts single phase	Watt	Amps	Width	Ship Weight ^o
GR2AL-18	120	370	3.1	GR2AHL-18	120	470	3.9	21.5" (546 mm)	28 lbs. (13 kg)
	120/208		2.2		120/208		2.7		
	120/240		2.0		120/240		2.5		
GR2AL-24	120	470	3.9	GR2AHL-24	120	620	5.2	27.5" (699 mm)	32 lbs. (15 kg.)
	120/208		2.7		120/208		3.4		
	120/240		2.5		120/240		3.1		
GR2AL-30	120	570	4.8	GR2AHL-30	120	780	6.5	33.5" (851 mm)	35 lbs. (16 kg.)
	208		3.2		208		4.2		
	240		2.9		240		3.8		
GR2AL-36	120	755	6.3	GR2AHL-36	120	980	8.2	39.5" (1003 mm)	37 lbs. (17 kg.)
	120/208		4.3		120/208		5.3		
	120/240		3.9		120/240		4.8		
GR2AL-42	120	855	7.1	GR2AHL-42	120	1130	9.4	45.5" (1156 mm)	53 lbs. (24 kg.)
	120/208		4.7		120/208		6.1		
	120/240		4.3		120/240		5.5		
GR2AL-48	120	1040	8.7	GR2AHL-48	120	1340	11.2	51.5" (1308 mm)	64 lbs. (29 kg.)
	120/208		5.8		120/208		7.3		
	120/240		5.3		120/240		6.6		
GR2AL-54	120	1165	9.7	GR2AHL-54	120	1490	12.4	57.5" (1460 mm)	74 lbs. (34 kg.)
	120/208		6.4		120/208		8.0		
	120/240		5.9		120/240		7.2		
GR2AL-60	120	1350	11.3	GR2AHL-60	120	1700	14.2	63.5" (1613 mm)	83 lbs. (38 kg.)
	120/208		7.5		120/208		9.2		
	120/240		6.9		120/240		8.3		
GR2AL-66	120	1460	12.2	GR2AHL-66▼	120	1860	15.5	69.5" (1765 mm)	93 lbs. (42 kg.)
	120/208		8.1		120/208		10.0		
	120/240		7.3		120/240		9.0		
GR2AL-72	120	1635	13.6	GR2AHL-72▼	120	2085	17.4	75.5" (1918 mm)	101 lbs. (46 kg.)
	120/208		9.1		120/208		11.3		
	120/240		8.3		120/240		10.2		
GR2AL-84▲	120	1920	16.0	GR2AHL-84▲	120	2320	19.3	87.5" (2223 mm)	123 lbs. (56 kg.)
	120/208		10.7		120/208	2470	13.4		
	120/240		9.8		120/240	2470	12.0		

^o Shipping weight includes packaging, and does not include RMB, must order an RMB.

▲ 120 volt models require additional switches and tandem (end-to-end) elements.

▼ 120 volt models with infinite controls require additional switch(es) and tandem (end-to-end) elements.

NOTE: Units rated for 120/208 or 120/240 volt are manufactured with a 120 volt circuit for the incandescent lights and a 208 or 240 volt circuit for the heating element(s).

HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A.

(800) 558-0607 | (414) 671-6350 | www.hatcocorp.com | support@hatcocorp.com | intlsales@hatcocorp.com



Glo-Ray® Infrared *Designer* Aluminum Strip Heaters with Lights

Models: GR2AL -18, -24, -30, -36, -42, -48, -54, -60, -66, -72, -84

GR2AHL-18, -24, -30, -36, -42, -48, -54, -60, -66, -72, -84

SWITCH LOCATION

Remote only

TOGGLE SWITCH

Amps: Max. 15 amps

INFINITE SWITCH

Max. 12.2 amps

LEADS

5' (1524 mm) through 0.5" (13 mm) conduit in Stand cavity is standard

ELEMENT HEIGHT REQUIREMENTS

(Refer to the *Installation* section of the *Manual* on the *Hatco* website)

Standard Watt

Height: 8"-12" (203-305 mm)

Target Width: 12"-14" (305-356 mm)

High Watt

Height: 11"-14" (279-356 mm)

Target Width: 14"-16" (356-406 mm)

REMOTE CONTROL ENCLOSURES

Must order one RMB control box per Strip Heater - If RMB2 is used, multiple warmers can be controlled from one box. For more details, see "Choose Remote Box" section listed under "Resources" on the *Hatco* website, www.hatcocorp.com

Model	Width	Switches
RMB-3	6" (150 mm)	2 toggles
RMB-7	9.375" (239 mm)	2 toggles with pilot lights or 1 toggle, 1 infinite and pilot light
RMB2-1R	11" (279 mm)	1 toggle, 1 infinite, 1 relay, 1 indicator light
RMB2-2R	14" (356 mm)	1 toggle, 1 infinite, 2 relays, 1 indicator light

PRODUCT SPECS

Designer Infrared *Designer* Aluminum Foodwarmer with Lights

The Infrared *Designer* Aluminum Foodwarmer with Lights shall be a Glo-Ray®, manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A. The foodwarmer shall be a Glo-Ray model ... , rated at ... watts, ... volts, single phase and be ... inches (millimeters) in overall width. The Glo-Ray shall consist of an aluminum housing and include as standard equipment 14" (356 mm) *Designer* Stands. The infrared heating element shall be tubular metal sheathed. The foodwarmer shall be factory assembled ready for electrical installation.

Options shall include *Designer* Color Housing, *Designer* Color Inset Panel, *Designer* non-adjustable Stands in various sizes (available in *Designer* Colors), Overhead Mounts (available in *Designer* Colors), dark gray *Designer* corner caps, sneeze guards, no Control, no Bulbs, Extra Lamps, Extended Electrical Power Leads, and Remote Control Box.

24/7 service in U.S. and Canada only.

HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A.

(800) 558-0607 | (414) 671-6350 | www.hatcocorp.com | support@hatcocorp.com | intlsales@hatcocorp.com