Drawer Warmers

Cafeterias • Convenience Stores Restaurants & Cafés • Clubs & Bars • Concessions



HDWTC-2 pg. 154



HDW-2 with 6" deep food pans pg. 155



HDW-2B in optional *Designer* Warm Red pg. 155



HDW-1.5R2 with optional touchscreen contro pg. 155



CDW-3N pg. 157



HRDW-2U-1 with standard utensil well and utensil pan (lid and pot not included) pg. 158



Heated Drawer Warmers with Top Control

Hatco Drawer Warmers ensure optimal holding of a variety of products at safe temperatures, while minimizing moisture loss and texture change. Our unique blanket element design promotes uniform temperatures throughout the cavity. Each drawer features adjustable sliding vents. Touchscreen controller controls temperature and time for each drawer individually.

- Top-of-the-unit touchscreen controller is positioned at an angle for greater visibility
- Controller provides individual temperature control and hold timer for each drawer with visual and audio alerts
- Robust stainless steel construction inside and out
- Drawer frame is constructed of heavy duty, 12 gauge stainless steel and drawers slide on durable nylon rollers
- Easy-to-clean seamless interior core

- Snap out side panels make this unit easy to clean and service
- Drawer frame can accommodate varying pan configurations, including full size, half size or one-third size pans up to 6" deep, with or without lids
- Pans lift straight up, eliminating the need to tilt pan for removal
- USB port for easy software updates
- Unit comes standard with removeable 4"plastic legs



NEMA 5-15P

217 lbs

HDWTC-2

shown with Accessory 2" casters (4" plastic legs are standard)

HEATED DRAWL	ER WARMERS WITH TOP C	ONTROL			
Model	Dimensions ↔ W x D x H	Voltono	Watts	Dlug	Approx.
woder	WXUXU	Voltage	walls	Plug	Ship Weight
HDWTC-1	24 ¹ / ₂ " x 25 ⁵ / ₈ " x 11 ¹¹ / ₁₆ "	120	353	NEMA 5-15P	120 l bs
HDWTC-2	24 ¹ / ₂ " x 25 ⁵ / ₈ " x 20 ¹ / ₈ "	120	704	NEMA 5-15P	178 lbs

120


1055

All Heated Drawer Warmers with Top Control Models Feature:

HDWTC-3

Models Shipped with: One 6" deep food pan per drawer, 4" plastic legs, 6' cord and plug. Cord Location: top, back-left side, recessed to protect plug.

OPTIONS (available at time of purchase only) **OS-PAN** Oversized Drawer Frame and Pan (20" x 15" x 5") in lieu of standard Drawer with Pan ACCESSORIES (available for purchase at any time) **HDW-TRIVET** Custom trivet raises food product ½" off bottom of full size pan (17½" x 9½" x ½") HDW 6" LEG 6" adjustable stainless steel Legs HDW-CASTER-2 2" Dia. Casters - all swivel, 2 lock - adds 21/2" to height of unit 3" Dia. Locking Casters – all swivel, all lock – adds 41/4" to height of unit HDW-CASTER-3 5" Dia. Locking Casters - all swivel, all lock - adds 61/4" to height of unit HDW-CASTER-5



FOOD PANS AND TRIVETS - PAGE 245

^{24&}lt;sup>1</sup>/₂" x 25⁵/₈" x 28⁷/₁₆" ↔ Add 1%" to depth for drawer handle. Height does not include standard 4" plastic legs.

Drawer Warmers

Hold everything from meat to vegetables to rolls in the Hatco Drawer Warmers. Built for tough kitchen duty with rugged construction and heavy-duty hardware, these warmers keep a variety of foods hot and fresh until served.

- Standard and narrow widths
- 1-, 2-, 3- or 4-drawer freestanding or 1-, 2- or 3-drawer built-in models
- Completely insulated individual cavities provide maximum energy efficiency (excludes HDW-1R2,-2R2)
- Each drawer has a food pan, recessed individual thermostatic control, temperature monitor, vent slides and power switch
- 12-gauge stainless steel heavy-duty drawer slides with nylon rollers
- Available with: oversized drawer frame, biscuit pan drawer, chip guard, casters, 6" adjustable stainless steel legs, water/ spillage pan and splash baffle
- Standard width Drawer Warmer pans lift straight out of drawer (HDW-1N, -2N, -3N and HDW-1R2, -1.5R2, -2R2 models requiring tipping the pan to install)








HDW-2 with Accessory 6" stainless steel legs







HDW-1.5R2 with optional touchscreen control

FREESTANDING DRAWER WARMERS

Model	Dimensions ↔ W x D x H	Voltage Single Phase	Watts	Approx. Ship Weight
HDW-1	29½" x 22¾" x 11"	120, 208, 240	450	97 lbs.
HDW-2	29½" x 22¾" x 21½"	120, 208, 240	900	168 lbs.
HDW-3	29½" x 225%" x 31¼"	120, 208, 240	1350	232 lbs.
HDW-4*	29½" x 22¾" x 41¾"	120, 208, 240	1800	296 lbs.
HDW-1N	201/8" x 27" x 11"	120, 208, 240	450	83 lbs.
HDW-2N	201/8" x 27" x 211/8"	120, 208, 240	900	168 lbs.
HDW-3N	201/8" x 27" x 311/4"	120, 208, 240	1350	223 lbs

[↔] Add 13/8" to depth for drawer handle. Height does not include standard 4" plastic legs.

All Freestanding Drawer Warmer Models Feature:

Plug: NEMA 5-15P. (208 and 240V use NEMA 6-15P).

HDW-4 Shipped with: 6" stainless steel legs.

Models Shipped with: One 6" deep food pan per drawer, 4" plastic legs, 6' cord and plug. Cord Location: Back of unit, lower left corner.

SPLIT DRAWER WARMERS

Model	Dimensions ↔ W x D x H	Voltage Single Phase	Watts	Approx. Ship Weight
HDW-1R2	281/8" x 165/8" x 107/8"	120	690	90 lbs.
HDW-1.5R2	281/8" x 161/2" x 151/2"	120	990	112 lbs.
HDW-2R2	281/8" x 165/8" x 20"	120	1290	135 lbs.

Add 13/6" to depth for drawer handle. Height does not include standard 4" plastic legs.

All Split Drawer Warmer Models Feature:

Plug: NEMA 5-15P.

HDW-1R2 shipped with: Two 2½" deep food pans, 4" legs, 6' cord and plug. HDW-1.5R2 shipped with: Three 2½" deep food pans, 4" legs, 6' cord and plug. HDW-2R2 shipped with: Four 2½" deep food pans, 4" legs, 6' cord and plug. Pan Capacity: 20¾"W x 12¾"D x 2½"H.

Cord Location: Back of unit, lower left corner.

BUILT-IN DRAWER WARMERS

Model	Dimensions ↔ W x D x H	Voltage Single Phase	Watts	Approx. Ship Weight
HDW-1B	281/4" x 223/8" x 97/8"	120, 208, 240	450	88 lbs.
HDW-2B	281/4" x 223/8" x 20"	120, 208, 240	900	159 lbs.
HDW-3B	281/4" x 223/8" x 301/6"	120, 208, 240	1350	232 lbs.
HDW-1BN	19½" x 26¾" x 9¾"	120, 208, 240	450	88 lbs.
HDW-2BN	19½" x 26¾" x 20"	120, 208, 240	900	159 lbs.
HDW-3BN	19½" x 26¾" x 30½"	120, 208, 240	1350	232 bs.


[→] Add 13%" to depth for drawer handle. Width and Height excludes front mounting flange.

All Built-In Drawer Warmer Models Feature:

Conduit: 4' flexible conduit.

Models Shipped with: One 6" deep food pan per drawer.


OPTIONS AND ACCESSORIES - PAGE 156



BUILT-IN CUTOUT REQUIREMENTS

Model	Width	Depth▼	Height
HDW-1B	28%"	24"	101/8"
HDW-2B	28%"	24"	201/4"
HDW-3B	28%"	24"	30¾"
HDW-1BN	19¾"	28¾"	101/8"
HDW-2BN	19¾"	28¾"	201/4"
HDW-3BN	19¾"	28¾"	30%"

[▼] Depth includes 1½" for conduit connector.



Not available for Canada.



OPTIONS (available at time of purchase only)

Designer Drawer Front colors per drawer (not available for HDW-1R2, -1.5R2, -2R2 models) Non-standard colors are non-returnable – Stainless steel standard

otamaara ot	one are non-returnable etanness etcor etanaara
RED	Warm Red
BLACK	Black
GRAY	Gray Granite
WHITE	White Granite
NAVY	Navy Blue
GREEN	Hunter Green
COPPER	Antique Copper
HDW-TTC	Temperature Control Timer – 6-channel control touchscreen display
OS-PAN	Oversized Drawer Frame and Pan (20" x 15" x 5") in lieu of
	standard Drawer with Pan, standard width models only
	(excludes HDW-1R2, -1.5R2, -2R2)
BIS DRAWER	Biscuit Pan Drawer – accommodates two 18" x 13"
	Half-Size Sheet Pans (not included) in lieu of standard Drawer
	with Pan, standard width models only
	(excludes HDW-1R2, -1.5R2, -2R2)
HDW-CHIP	Chip Guard (excludes HDW-1R2, -1.5R2, -2R2)
RD-NOVENT	No Drawer Vents (HDW-1R2, -1,5R2, -2R2 only)

ACCESSORIES (available for purchase at any time)

HDW-TRIVET	Custom trivet raises food product ½" off bottom of		
UDM-INME!			
	full size pan 17½" x 9½" x ½"		
HDW 6" LEG	6" Adjustable Stainless Steel Legs, standard on HDW-4		
	(excludes HDW-1R2, -1.5R2, -2R2)		
HDW-CASTER-2	2" Dia. Casters – all swivel, 2 lock – adds 2½" to height of unit,		
	HDW-1, -2, -3 models only (excludes HDW-1R2, -1.5R2, -2R2)		
HDW-CASTER-3	3" Dia, Locking Casters – all swivel, all lock –		
	adds 41/4" to height of unit, HDW-1, -2, -3 models only		
	(excludes HDW-1R2, -1.5R2, -2R2)		
HDW-CASTER-5	5" Dia. Locking Casters – all swivel, all lock –		
	adds 61/4" to height of unit (excludes HDW-1R2, -1.5R2, -2R2)		
HDW-SPILL	Water/Spillage Pan – one per drawer		
	(excludes HDW-1R2, -1.5R2, -2R2 and BIS Drawer, and OS-Pan Options)		
HDW-SPLASH	Splash Baffle – one per drawer		
	(excludes HDW-1R2, -1.5R2, -2R2 and BIS Drawer, and OS-Pan Options)		

FOOD PANS AND TRIVETS – PAGE 245 COLORS AND FINISHES – INSIDE BACK COVER



HDW-TRIVET



CASTERS
HDW-CASTER-2 all swivel, 2 lock
HDW-CASTER-3 all swivel, all lock
HDW-CASTER-5 all swivel, all lock



HDW 6" LEG







HDW-TTC OptionShown: Temperature adjustment and timer touchscreen control




Biscuit Pan Drawer (pans not included) **BIS DRAWER** Option



Additional Humidity

- A. Stainless Steel Food Pan
- B. Splash Baffle
 - HDW-SPLASH accessory
- C. Water/Spillage Pan (add 1/4" of water) **HDW-SPILL** accessory



Prevents chips from reaching the element

- D. Heat Shield (included)
- E. Heating Element (included)
- F. Chip Guard **HDW-CHIP** Option (Standard width shown)

Convected Drawer Warmer

This drawer warmer is designed to keep a variety of food products hot and flavor-fresh until served. With a single non-humidified cavity and a single electronic temperature control, this unit provides even, dry heat for food products that do not require humidity. With insulated top, sides and back, they provide excellent energy efficiency.

- Digital electronic controller for easy programming
- Low velocity convected air system provides even temperature throughout the cabinet
- Tough, durable chrome handles that are angled to avoid contact from passing carts



- Narrow width fits most kitchen footprints
- Heavy-duty drawer slides with nylon rollers
- Includes three full-size pans
- Provides even, dry heat for food products that do not require humidity.

CONVECTED DRAWER WARMER					
Model	Dimensions ↔ W x D x H	Voltage Single Phase	Watts	Approx. Ship Weight	
CDW-3N	16%" x 283/32" x 271/2"	120	1015	179 lbs.	

[↔] Add 1¾" to depth for drawer handle. Height does not include casters, which add 21/2" to height.

All Convected Drawer Warmer Models Feature:

Plug: NEMA 5-15P.

Models Shipped with: One 6" deep food pan per drawer, low profile 2" diameter casters, 6' cord and plug. Cord Location: Back of unit, top right corner.

FOOD PANS AND TRIVETS - PAGE 245





Heated Rice Drawer Warmers


Hatco's Heated Rice Drawer Warmers are designed to keep rice hot and at desired consistency until served.

It holds rice in the same pot it's prepared in, reducing pan-to-pan transfer time and labor.

With a digital electronic temperature control, this unit provides even heat throughout the holding cavity. With all around insulation, these drawer warmers provide excellent energy efficiency.

- Drawers accept Panasonic 23 cuprice pots (pots and lids not available)
- Drawers accept Town 30 cup rice pots with accessory Town 30 cup pot drawer adapters (pots and lids not available)
- Allows one pot per drawer of cooked rice for long term holding, with the option of serving from third pot in top heated well (HRDW-2U-1 only)
- Stainless steel construction, including back panel, handles the rigors of daily kitchen use
- Heavy-duty drawers and robust telescopic drawer slides makes pan removal easy and efficient
- Stainless steel utensil well and utensil pan included with HRDW-2U and HRDW-2U-1 models only
- Adjustable t-stat with knob for optimal rice holding in top well (HRDW-2U-1 only)
- Raised beveled edge on top of HRDW-2, HRDW-2U models only





HRDW-2U-1 with accessory hinged lid and standard utensil well and utensil pan

HEATED RICE DRAWER WARMERS

Model	Dimensions ↔ W x D x H	Voltage Single Phase	Watts	Amps	Approx. Ship Weight
HRDW-2	20¼" x 22 ¹³ /16" x 351/8"	120	700	5.8	153 lbs.
HRDW-2U	20¼" x 22 ¹³ / ₁₆ " x 351/ ₈ "	120	700	5.8	150 lbs.
HRDW-2U-1	20¼" x 22 ¹³ /16" x 351/8"	120	1150	9.6	150 lbs.

^{**} Add 1%" to depth for drawer handle. Height does not include standard casters, which add 2.5" to height of unit

All Heated Rice Drawer Warmer Models Feature:

Plug: NEMA 5-15P.

Models Shipped with: Utensil pan (HRDW-2U and HRDW-2U-1 only), 4" casters, 6' cord and plug. Cord Location: Back of unit, upper left corner.



